



# 07/<sub>SLIDE</sub>

#### Mounting Accessory for the OILSPY Standard



This photo is an illustration of a specific slide.

## 4 fixing versions

o **Ref. 1603 :** 2 mounting brackets, up and down

o **Ref. 1710 :** Base plate pad

o **Ref. 1641 :** Dead weight (50 kg)

o **Ref. 1951 :** Bottom mounting only

O Slides for specific applications on request

## **Specifications**

 Material : guiding tubes : Stainless steel AISI 316L

o Guiding tubes length:

- 1603, 1641 et 1710 versions :

Min: 1m Max: 6m

- 1951 versions:

Min: 0.75m Max: 1m

The Slide is a mounting accessory for the Standard **OILSPY** hydrocarbons detector.

The detector is attached to a floating assembly and guided vertically. It allows its use in space restricted sites with variable water levels:

 decanting basin, collector, output canal, aqueduct...

#### **Description**

- The slide is made of the guiding assembly (2 guides and 2 mountings high and low) and a float.
- Water level variation: +/- 70 cm around a medium level with a 2 meters long standard version (other lengths available upon request)
- o Material: Stainless steel AISI 316L
- For maintenance purposes, the floating assembly can be lifted by pulling the OILSPY's cable

	Total Standard mass (without buoy)	Mass of the buoy
1603	6.4 kg (2m)	
1710	5.7 kg (2m)	900g
1951	1.9 kg (1m)	
1641	59.217 kg (2m)	





